

Fagor Kore 900 Series Electric Fry Top FT-E905L

Quick Overview

- 2mm thick 304 S/S surface top
- Laser-cut joints, automaticÂ welding and polishes. ScrewsÂ are hidden from view
- Fry-tops manufactured inÂ 20 mm thick mild steel,Â high powered and with rapidÂ temperature attainment
- Rapid reaction and recoveryÂ times of the fry-topÂ temperature
- The fry-tops are integrated intoÂ the funnelled surface top
- The funnelled housing withÂ rounded edges and cornersÂ makes them very easy to clean
- Fry-top tilted towards theÂ front to facilitate fat and liquidÂ collection
- Fitted with an opening for theÂ collection of cooking fat andÂ storage tray with a capacity ofÂ up to 2L depending on the model
- Option of easily dismountableÂ side and back splash guards.
- High-temperature enamelledÂ cast iron flue protector
- Access to theÂ components from theÂ front
- Machines with IPX5 grade waterÂ protection
- Smooth hot-plate
- Electrically heated modelsÂ use stainless steel shieldedÂ heating elements; temperatureÂ controlled by a thermostat,Â between 100 and 300Â ° C
- Optional stands available

Description

Fagor Kore 900 Series Electric Fry Top FT-E905L

Key Features

- 2mm thick 304 S/S surface top
- Laser-cut joints, automatic welding and polishes. Screws are hidden from view
- Fry-tops manufactured in 20 mm thick mild steel, high powered and with rapid temperature attainment
- Rapid reaction and recovery times of the fry-top temperature
- The fry-tops are integrated into the funnelled surface top
- The funnelled housing with rounded edges and corners makes them very easy to clean
- Fry-top tilted towards the front to facilitate fat and liquid collection
- Fitted with an opening for the collection of cooking fat and storage tray with a capacity of up to 2L depending on the model
- Option of easily dismountable side and back splash guards.
- High-temperature enamelled cast iron flue protector

- Access to the components from the front
- Machines with IPX5 grade water protection
- Smooth hot-plate
- Electrically heated models use stainless steel shielded heating elements; temperature controlled by a thermostat, between 100 and 300 ° C
- Optional stands available

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Product Condition	New
Knobs	1 knob
Net Weight (Kg)	75
Width (mm)	400
Depth (mm)	930
Height (mm)	290
Packing Width (mm)	1022
Packing Depth (mm)	440
Packing Height (mm)	535
Power	415V, 7.5kW/3~N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice