# 2 Shelf Square Glass Roller Shutter Front Controls



## 2 Shelf Drop-in Refrigerated Display with Square Glass, Roller Shutter and Front Controls (solid back)

Chilled display units incorporating a cold well and 2 glass display shelves. The unique Versigen innovative “Polar Air Stream” system provides a constant, recirculating cold air curtain completely enveloping the food displayed. Holding pre-chilled food at a safe, regulated temperature while retaining taste and freshness. Perfect for sandwiches, fruit, yogurts and cold drinks. Self-contained units with accurate, digital control, automatic defrost, high pressure warning and automatic condensate evaporation. The Refrigeration System is housed underneath in a tidy, compact cradle. Utilising a highly efficient, naturally occurring, hermetically sealed, hydrocarbon gas type R290 as standard - reducing carbon footprint and energy consumption.

| Features |
| --- |
| Condensing unit set at 90°. Removes the need for unsightly vents in the front panels of serveries and counters. |
| Digital thermostat & temperature controller. |
| Sliding rear double glazed doors. |
| Advanced air flow design with unique polar airstream technology. |
| Controls conveniently positioned in the gantry hood. |
| Efficient, ozone friendly hydrocarbon refrigeration. |
| Long life, low energy LED. |
| Maintaining the core product temperature of pre-chilled food below 5°C in ambient condition not exceeding 25°C and 60% relative humidity. |
| Automatic condensate water evaporation [no need to empty drip trays). |
| Automatic defrost control. |
| 24 hour operation. |
| Fully insulated. |
| Plenum duct to aid onsite ventilation and installation. |

| Optional Extras |
| --- |
| Additional air flow kit [In-line fan and flexi ductkit for difficult non-standard installations] (Code: DRA) |
| Front Roller Blind (add “RB” to end of model code) |

## Model Specifications

| Model | Length | Depth | Height | Weight | Amp | Power (kW) |
| --- | --- | --- | --- | --- | --- | --- |
| D2RDLSAFC | 830 | 660 | 645 | 119 | 10 | 1.5 |
| D3RDLSAFC | 1158 | 660 | 645 | 140 | 10 | 1.5 |
| D4RDLSAFC | 1486 | 660 | 645 | 158 | 10 | 2.0 |
| D5RDLSAFC | 1814 | 660 | 645 | 179 | 10 | 2.5 |