Product Specification Sheet
WNC-BS2
Bed Room Station



WNC-BS2 Bed Room Station

The WNC-BS2 dual patient bedside station is equipped with a "Call Placed" LED indicator, a "Cancel" button, and two 1/4-inch jacks designed to connect call cords, bed exit sensors, or ventilator alarms. Each jack delivers an individual ID that registers separately at the master console upon activation.
Placing a call from the station updates the information screen on the Display Console and illuminates connected corridor lamps or zone lights. Alerts are triggered by pressing the call cord button or by the unintentional disconnection of the call cord from the faceplate jack.

Architects and Engineers Specification

The specification covers the wireless WNC-BS2 dual bed room station, designed with a "Call Placed" LED indicator, a "Cancel" button, and two 1/4-inch connection jacks suitable for call cords, bed exit monitors, or ventilator alarms. Each port operates with a unique identifier to report distinct signals back to the main console. Activating a connected call cord switch or inadvertently unplugging a cord triggers an alarm on the console, turns on the station's "Call Placed" LED, and illuminates any installed corridor or zone lights. For new construction projects, the unit mounts into a Carlon A52171D deep 4/S plastic enclosure equipped with a single-gang plastic mud ring.

Specification

- **Dimensions:**
  - Height: 4-1/2" (114mm)
  - Width: 2-3/4" (69mm)
  - Depth: 2-5/8" (66mm)
- **Panel:** Flame retardant GE Lexan faceplate (UL flame rating 94V0)
- **Batteries:** Two CR123A Lithium batteries
- **Backbox:** Carlon A52171D deep 4/S plastic back box with single gang plastic mud ring
- **Surface Mount:** Wiremold 2344 single gang enclosure (2-3/4" deep)
- **Flush Mount:** Single gang BB10L Cooper B-Line bracket

System Components

- **PC Server:** Video Display Console PC
- **MV500:** 500 Console Master
- **MV200 PLUS:** 200 PLUS Console Master
- **WNC-CC:** Call Cord, 1/4" Plug, 8 Ft. Length

Features

- Two unique ID numbers register Bed A and Bed B
- Simple push button calling
- Call Placed indicator
- Call-reset push button
- Call automatically registers if call cord is removed
- Call is displayed with patient or device name at console
- Call activates Corridor Lamp and Corridor Zone Lamp (if installed).

Toll-Free: 888.556.3998
Phone: 716.689.0871
Address: 5225 SHERIDAN DR STE 110,
GEORGETOWN SQUARE, WILLIAMSVILLE NY 14221-4952
E-mail: support@becsolutionsllc.com