Product Specification Sheet
WNC-DB
Kit Wireless Doorbell



WNC-DB Kit
Wireless Doorbell

The WNC-DB can be used as an outdoor wireless doorbell or in any application where momentary push-button activation is required. A call from a WNC-DB station activates a pre-programmed call information display at the Video Display Console.
If configured in system programming, pressing the WNC-DB button will additionally provide notification to associated pocket pagers or two-way radios, as well as activate the associated Corridor Lamp and Corridor Zone Lamp if installed.

Specifications

Dimensions:
- Height: 4-1/2" (114 mm)
- Width: 2-13/16" (72 mm)
- Depth: 1-5/8" (41 mm)

Panel: Flame retardant GE Lexan faceplate (UL flame rating 94V0)
Batteries: One CR123
Surface Mount: Includes Carion 9801 plastic single-gang box (2.75" deep)

Features

- Simple operation
- Reliable waterproof momentary switch
- Flame retardant GE Lexan faceplate
- Supervised for battery voltage and operation
- Includes weatherproof housing for outdoor use

Architects' and Engineers' Specifications

Outdoor push button station shall be WNC-DB or approved equal. It shall be surface mounted and provide a button for push-button activation. The button shall be a waterproof momentary switch and shall not require a reset at the station.

Pressing the button shall activate a call information display at the console as well as any associated pocket pagers or two-way radios. The push button shall be capable of being configured in programming to activate the associated corridor light and corridor zone light, if installed.

System Components

PC Server: Video Display Console
MV500: WNC 500Z Console
MV200Plus: WNC 2002 Plus
SPS5: Pocket Pager Transmitter
WNC-DL Series: Corridor Light System

Toll-Free: 888.556.3998
Phone: 716.689.0871
Address: 5225 SHERIDAN DR STE 110,
GEORGETOWN SQUARE, WILLIAMSVILLE NY 14221-4952
E-mail: support@becsolutionsllc.com