Product Specification Sheet
WNC-DL2WR
LED Corridor Lamp



WNC-DL2WR LED Corridor Lamp

The WNC-DL2WR LED Corridor Lamp listed to UL1069 edition 7 is an intelligent device equipped with a clear and a red long life LED. It provides a visual indication of up to four types of devices from a patient room or associated transmitters when connected to a WNC-DLC series listed Controller/Power Supply on a listed WNC-SERVER-UL1069 Wireless Nurse Call System. Emergency calls(smoke, bathroom) are indicated by the rapid flashing of WNC-DL2WR red LED, routine calls produce a steady illumination and the white LED and additional devices can be assigned to annunciate white flashing and red steady lights. The LED's are housed in a translucent enclosure mounted on a fog white, ABS plastic panel. All corridor lights connect in parallel to the WNC-DLC series listed dome light controller/power supply on a single pair of 18 AWG wires.

Architects' and Engineers' Specifications

The two color corridor/zone LED lamp which is the WNC-DL2WR and shall be listed to UL1069 Edition 7 listed for "Hospital Signaling and Nurse Call Equipment." Each corridor light shall include a translucent plastic cover mounted on a flame retardant ABS plastic panel which shall be removable for LED replacement without the use of mounting screws. The WNC-DL2WR corridor/zone light shall provide a clear LED that provides a rapid flash to annunciate emergency calls, a steady illumination to annunciate routine calls and a red LED assignable in system programming to any other transmitter device such as a smoke detector. All corridor lights shall connect in parallel to the WNC-DLC series listed dome light controller/power supply on a single pair of 18 AWG wire. Systems that require more than two conductor wire or require individual "home run" wire from each light or that require an AC outlet for each light are not acceptable.

Specifications

- **Dimensions:**
  Height: 4.66"
  Width: 4.81"
  Depth: 2.68"
  Weight: 7 oz
- **LED:** 5VDC
- **Power:** 24 VDC, 14mA
- **Finish:** Translucent white plastic cover mounted on a flame retardant, fog white ABS plastic panel.
- **Mounting:** Double gang plaster ring or double gang ring with double gang box
- **Wiring:** 2 conductor, 18 AWG up to 300 feet run

System Components

WNC-SERVER-UL1069: Computer Console
WNC-DLC: Corridor Light Power Supply
WNC-965: Wireless Universal Transmitter
WNC-PC-UL1069: Wireless Emergency Pull Station
WNC-BS2-UL1069: Dual Bedside Patient Station
MV500: Wireless Emergency Console

Features

- Listed to UL1069 Ed. 7 Hospital Signaling & Nurse Call Equipment
- Can also be used as a zone light
- Snap in lens
- Two long life LED indicators (clear and red)
- Flame retardant, fog white, ABS plastic panel

Note: With the wireless system, you can only use dome lights with the MV400, MV500 and the WNC-Server2. They cannot be used with the MV200 or PLUS

Toll-Free: 888.556.3998
Phone: 716.689.0871
Address: 5225 SHERIDAN DR STE 110,
GEORGETOWN SQUARE, WILLIAMSVILLE NY 14221-4952
E-mail: support@becsolutionsllc.com