Product Specification Sheet
WNC-SS
Staff Assist Station



Architects' and Engineers' Specifications

The wireless staff assist pull station shall be Systems Technologies Vision Link part number WNC-SS and shall be ETL Listed, conforming to UL1069 Edition 7 for "Hospital Signaling and Nurse Call Equipment." The Staff Assist Station shall be fully supervised for operation and low battery. Station shall consist of a plastic faceplate with large, green "Staff" reed switch for activation, quality assurance LED and an embedded transmitter with batteries.

Unit shall be waterproof and shall include a gasket for use in procedure rooms, bathrooms, showers and other wet areas. Operation of emergency signal shall be accomplished by a short pull on the nylon cord supplied with the station or by pulling down on the slide lever marked "Staff". Once an emergency staff assist call has been placed the red LED indicator will continue to flash until the station is re-set.

Equipment Options

WNC-SERVER: Video Display Console
WNC-DLC: Corridor Light Power Supply
WNC-DL1W: LED Corridor/Zone Light
WNC-DS: Duty Station

WNC-SS
Staff Assist Station

The WNC-SS is a wireless single gang Staff Assist pull station for use in any location where activation of an emergency signal is required. The station features an embedded transmitter with a large, green "Staff" reed switch for activation and may be used in any location where a staff emergency signal is required including showers, procedure rooms and other wet areas. It is waterproof for showers and other wet areas with the addition of a gasket. The pull cord supplied may be used for staff emergency activation, or if desired, the slide switch may be activated. The station features a "call placed" LED indicator that will continue to flash until the station is re-set.

Specifications

- **Dimensions:**
  Height: 4-1/2" (114mm)
  Width: 2-13/16" (72mm)
  Depth: 1-5/8" (41mm)
  Projects 11/16" (17mm) from mounting surface (including pull down lever)
- **Weight:** 5.2 oz
- Panel: Flame retardant GE Lexan faceplate (UL flame rating 94V0)
- **Batteries:** Three CR123
- **Backbox:** Carlon B120A plastic single gang box
- **Flush Mount:** Cooper BB10L single gang B-Line bracket
- **Surface Mount:** Leviton 42777 - 1WA plastic single gang box (1.75" deep) with use of included gasket

Features

- ETL Listed, conforming to UL 1069 Edition 7
- Call-cancel at point of origin
- Flame retardant GE Lexan faceplate
- Pull cord or slide switch activation
- Waterproof with the addition of gasket
- Reliable reed switch
- Red LED alarm indicator

Toll-Free: 888.556.3998
Phone: 716.689.0871
Address: 5225 SHERIDAN DR STE 110,
GEORGETOWN SQUARE, WILLIAMSVILLE NY 14221-4952
E-mail: support@becsolutionsllc.com